

Copyright c. 2010. Tutti i diritti sulle immagini ed i testi sono riservati. Sono vietate la riproduzione e diffusione, anche parziale, in qualsiasi forma, delle fotografie e dei testi. I trasgressori saranno perseguiti a norma di legge. Tutti i prodotti illustrati costituiscono creazione di proprietà della società Gruppo Piazzetta SpA. Ogni diritto di sfruttamento dei modelli è riservato. I/i marchio/i ed i segni distintivi della società sono di proprietà esclusiva della satessa.



MA 262 SL

GENERAL TECHNICAL CHARACTERISTICS

- Structure:** enamelled steel, closed firebox
- Firebox:** in Aluker®
- Fire pit:** in cast iron
- Hood:** in steel
- Opening:** door in enamelled steel with self-cleaning ceramic glass resistant up to 750 C°.
- Rise n fall door,** hinged opening for cleaning
- Door profile:** in enamelled steel
- Door handle:** in enamelled steel
- Primary air:** adjustable manually
- Secondary air:** fixed
- Flue outlet:** top
- Flue damper:** manual
- Ash pan:** removable
- Fuel:** wood
- Heating:** radiant and natural convection

TECHNICAL DATA

Room heating capacity (min-max)	m ³	200 - 345
Nominal thermal efficiency	%	> 70
Rated heat output	kW	12
Consumption at rated heat output	Kg/h	4,5
Maximum heat output	kW	13
Maximum consumption	Kg/h	5,3
Flue outlet	Ø cm	25
Flue up to 4,5 mt	Ø cm	30
Flue over 4,5 mt	Ø cm	25
Fresh air intake (recomm. min sect.)	cm ²	300
Weight	Kg	235

ON REQUEST

- Cooking Pro kit
- Adjustable legs kit
- Positioning handles kit

Laboratory data using beech wood with less than 20% moisture content. Consumptions may vary according to the type of wood used



The availability of models may vary from Country to Country.

Compatible Cover

NETTUNO - EASY - CAGLIARI - ALGHERO

TECHNICAL DRAWING

