



MA 260 SL

GENERAL TECHNICAL CHARACTERISTICS

Structure: enamelled steel, closed firebox
Firebox: in Aluker®
Fire pit: in cast iron
Hood: in steel
Opening: door in enamelled steel with self-cleaning ceramic glass resistant up to 750 C°. Rise n fall door, hinged opening for cleaning
Door profile: in enamelled steel
Door handle: in enamelled steel
Primary air: adjustable manually
Secondary air: fixed
Flue outlet: top
Flue damper: manual
Ash pan: removable
Fuel: wood
Heating: radiant and natural convection

TECHNICAL DATA

| | | |
|--------------------------------------|-----------------|-----------|
| Room heating capacity (min-max) | m ³ | 210 - 360 |
| Nominal thermal efficiency | % | 75,5 |
| Rated heat output | kW | 12,5 |
| Consumption at rated heat output | Kg/h | 3,6 |
| Maximum heat output | kW | 13,5 |
| Maximum consumption | Kg/h | 4,2 |
| Flue outlet | Ø cm | 20 |
| Flue up to 4,5 mt | Ø cm | 25 |
| Flue over 4,5 mt | Ø cm | 20 |
| Fresh air intake (recomm. min sect.) | cm ² | 200 |
| Weight | Kg | 157 |

ON REQUEST

- Cooking Pro kit
- Adjustable legs kit
- Positioning handles kit

Laboratory data using beech wood with less than 20% moisture content. Consumptions may vary according to the type of wood used



The availability of models may vary from Country to Country.

Compatible Cover

ESSEN - AMBURGO - LUBECCA - BREMA - FRIBURGO - LIPSIA - VIENNA -
 COLONIA - DRESDA - ACADEMY - CLASS - EASY - VISION - NOVARA - TOKIO -
 OLIVETO - ATENE - ISTRIA - MERANO - VENEZIA - PAVIA - VALENCIA - OVIEDO -
 ASTI - ARGO - BARGA - VICENZA - LIVIGNO - IMOLA - VIAREGGIO - VIPITENO

TECHNICAL DRAWING

